

DESCRIPTION OF CORNER EVIDENCE FOUND

NO EVIDENCE FOUND—POSITION OF CORNER DETERMINED BY SINGLE PROPORTIONATE MEASUREMENT BETWEEN FOUND SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET A 5/8" X 24" REBAR WITH A DUCHESNE COUNTY 2½" DIA. ALUMINUM CAP AT THE POSITION OF THE WITNESS CORNER. ALSO SET REFERENCES AS SHOWN



MARKINGS ON MONUMENT

STATE PLANE COORDINATE DATA SOF WITNESS CORNER

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7225793.303 E: 1843579.431 NAVD88 EL: 6766.63'

LATITUDE: 40°09'15.86740" N 110°46'23.27128" W LONGITUDE:

ELLIPSOID HEIGHT: (GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

6713.265'

UT300040S0080W0_440600



PHOTO OF CORNER FACING WEST

CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

17 MAY'19

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

